

Shortwave Diathermy

Auto*Therm 390

Auto*Therm 390 Auto*Therm® 390 is a continuous and pulsed shortwave diathermy. This unit can be easily carried between treatment rooms or to the patient. The 390 utilized rubber plate capacitive electrodes. Capacitive electrodes are ideal for treating shallow areas and provide an affordable version of SWD. The basic unit comes with 2 soft-rubber capacitive applicators, 6 felt spacers, 2 cloth covers, 2 elastic straps, power cord and instructions.

Weight : 15 lbs. (6.8 kg) **Dimensions :** 7 in. (H) x 14 in. (W) x 16.5 in. (D) (18 cm (H) x 36 cm (W) x 42 cm (D))
Warranty : 2 years, one year on applicators and accessories



Auto*Therm 391

Auto*Therm 391 Auto*Therm® 391 combines the ME 390 with an arm, 14 cm inductive coil applicator and heavy-duty cart with ample storage space. Using this model, you will be able to choose from two different modes of application—the deep penetration of inductive coil diathermy or the shallower capacitive plates.

Weight : 60 lbs. (27.3 kg) **Dimensions :** 37 in. (H) x 19 in. (W) x 19 in. (D) (95 cm (H) x 48 cm (W) x 48 cm (D)) **Warranty :** 2 years, one year on applicators and accessories



Auto*Therm 395

Auto*Therm 395 The Auto*Therm 395 features continuous and pulsed shortwave diathermy. This advanced unit has eight different treatment applicators available: three inductive coils applicators, three spaced capacitive sets and two soft, flexible plate electrodes. High performance, multi-jointed arms lock in place for ease of use and safety. Each Auto *Therm 395 comes complete with two treatment arms, two 13 cm diameter capacitive applicators and cables and one 14 cm diameter inductive coil applicator and cable. **Weight :** 99 lbs. (45 kg.) **Dimensions :** 33.5 in. (H) x 15 in. (W) x 15.4 in. (D) (85 cm (H) x 38 cm (W) x 39 cm (D)) **Warranty :** 1 year



Item Description :

- 3953 Soft rubber applicator set 1-3.1 x 5.5 in. (8 x 14 cm)
- 3955 3.1 in. (8 cm) diameter coil applicator without cable, 30 W max
- 3956 5.5 in. (14 cm) diameter inductive coil applicator without cable, 90 W max
- 3958 Triplode coil applicator with cable, 200 W max
- 3959 1.6 in. (4.2 cm) diameter capacitive applicator, 21 W max
- 3960 3.3 in. (8.5 cm) diameter capacitive applicator, 80 W max
- 3961 5.1 in. (13 cm) diameter capacitive applicator, 200 W max
- 3962 3.1 x 5.5 in. (8 x 14 cm) soft-rubber applicator, 21 W max
- 3963 4.7 x 7.1 in. (12 x 18 cm) soft-rubber applicator, 80 W max

